




EMSHIELD WFR2 SYSTEM

Fire / Water / Movement / Sound



Product Description

EMSHIELD WFR2 features two water-repellant silicone sealing surfaces each adhered to fire-retardant impregnated foam backing and intumescent bellows. Because of the symmetrical design, either side can face out from an exterior or interior wall and maintain a 2-hour fire-rating. When either (or both) faces have a field-applied band of silicone that face is watertight.

The system is installed into epoxy adhesive field-applied to the sides of the foam and on the joint faces. An optional field-injected silicone sealant band seals the bellows to the substrate at the installation surface providing watertightness. Joins between each stick are executed using a field-applied silicone sealant at bellows' edge of the joint and field-applied intumescent sealant on the adjoining faces to the silicone.

Watertight, 2-Hour Fire-Rated, Sound Attenuating Energy-Efficient Wall Expansion Joint

EMSHIELD WFR2 is a fire-rated, watertight, sound-attenuating, energy-efficient primary seal for both retrofit and new structural expansion joints in vertical-plane applications.

EMSHIELD WFR2 eliminates the need for additional fire blankets, mineral wools, liquid sealants, cover plates, or other fire stopping materials.

For joints from 1/2-inch (12mm) up to 6-inches (150mm) where +25% and -25% (total 50%) of nominal material size joint movement is expected.

EMSHIELD WFR2 (Wall, Fire-Rated 2-Hours) continues with the EMSHIELD comprehensive line of breakthrough, multifunction, structural expansion joint materials being released by EMSEAL. Tested and certified by Underwriters Laboratories (UL), to the rigors of UL 2079, it can work in conjunction with the EMSHIELD horizontal fire-rated deck expansion joint, DFR2.

Fire-retardant-impregnated foam is factory pre-coated on both facing sides with an intumescent fireproofing material. Each side then receives a top coat of waterproof silicone. The resulting composite is then factory compressed to less than its nominal size for installation into structural or other openings.

Uses

For expansion joints in exterior and interior walls where a combination of watertightness, fire-rating, sound attenuation and thermal-efficiency are required. It can be used alone or under any other expansion joint cover, plate or filler where depth of substrate allows. Because it is coated on both sides it can face in either direction from the wall and maintain its performance characteristics within that wall. This increases the number of vertical applications in which it can be installed.

EMSHIELD WFR2 provides a watertight, clean handling, UV stable, nonstaining, low-temperature-flexible, high-temperature-stable, sound-attenuating, energy-efficient and fire-rated joint seal in a single installation process.

EMSHIELD WFR2 builds on EMSEAL's track record of over 30 years of innovation in sealing structural expansion joints with impregnated foam sealants.

Silicone-faced Intumescent Bellows
(Shown in an alternate color)

Fire Retardant Impregnated Foam

Silicone-faced Intumescent Bellows
(Available in 26 colors)



EMSHIELD WFR2



UL System WW-D-0091
UL System WW-D-0092
UL System WW-D-1079
UL System WW-D-1081
ULC System JF131
ULC System JF132

Features

Watertight – EMSHIELD WFR2 is installed with tensionless bellows, which when installed with an optional silicone bead on the weather face, maintains a watertight seal.

Fire-Rated – The fire-retardant-impregnated foam and intumescent bellows, when properly installed, ensure a 2-hour fire protection in accordance with UL-2079.

Sound Attenuation – EMSHIELD WFR2 minimizes sound transfer which often occurs at the expansion gap. The tested results for 1 1/2" WFR2 in an STC 68 / OITC 51 wall are an **STC value of 64** and an **OITC value of 52**.

Non-Invasive Anchoring – There are no hard metal-to-substrate connections with EMSHIELD WFR2. This includes embedded pins, anchors, screws, bolts or tracks, trays or rails, flanges or coverplates. The system is locked to the joint faces by means of the 1) backpressure of the foam; 2) the epoxy adhesive, and 3) the injected sealant bands at the joint face.

Movement Capability +25% and -25% (50% total) of nominal material size.

Joint-Size Variation – Uniform bellows appearance, and the ability to handle variations in joint size through size-switching, are among other system features.

Factory-Fabricated Transitions – as in all EMSEAL expansion joint systems, continuity of seal through changes in plane and direction is an essential performance differentiator.

EMSHIELD WFR2 is manufactured in straight-run sticks which can be joined in the field to EMSEAL's patent-pending factory-fabricated "Universal-90" Transitions. These are factory-fabricated single-piece 90° units which are coated on both sides with both luminescent and silicone coating allowing them to be installed as an upturn or downturn transition. Each has a 6-inch long horizontal leg and a 12-inch vertical leg. Transitions end in an uncoated 90° cut to be adhered to another transition piece as used in walls-to-decks, treads and risers, parapets, curbs and other applications.

In addition to guaranteeing watertightness, EMSEAL's Universal-90 transitions allow for much faster and secure installation by eliminating field cutting at angles.

Colors

The two silicone faces of EMSHIELD WFR2 can be manufactured of different colors to blend with their respective wall surfaces. EMSHIELD WFR2 is available in 26 standard colors which match the EMSEAL COLORSEAL line of products. Other custom silicone colors are available after consulting with EMSEAL.

Performance

Capable of movements of +25%, -25% (50% total) of nominal material size.

Standard sizes from 1/2" (12mm) to 6" (150mm).

Depth of Seal for all sizes = 4" (100mm).

Substrates must be solid, parallel and plumb.

Sizing

Product Code	Nominal Material Size (Joint Size @ Mean Temp.)	Depth of Seal
WFR2-50-100-02	1/2 " (12mm)	4 " (100mm)
WFR2-65-100-02	5/8 " (15mm)	4 " (100mm)
WFR2-75-100-02	3/4 " (20mm)	4 " (100mm)
WFR2-100-100-02	1 " (25mm)	4 " (100mm)
WFR2-125-100-02	1 1/4 " (30mm)	4 " (100mm)
WFR2-150-100-02	1 1/2 " (40mm)	4 " (100mm)
WFR2-175-100-02	1 3/4 " (45mm)	4 " (100mm)
WFR2-200-100-02	2 " (50mm)	4 " (100mm)
WFR2-225-100-02	2 1/4 " (55mm)	4 " (100mm)
WFR2-250-100-02	2 1/2 " (65mm)	4 " (100mm)
WFR2-275-100-02	2 3/4 " (70mm)	4 " (100mm)
WFR2-300-100-02	3 " (75mm)	4 " (100mm)
WFR2-325-100-02	3 1/4 " (85mm)	4 " (100mm)
WFR2-350-100-02	3 1/2 " (90mm)	4 " (100mm)
WFR2-375-100-02	3 3/4 " (95mm)	4 " (100mm)
WFR2-400-100-02	4 " (100mm)	4 " (100mm)
WFR2-425-100-02	4 1/4 " (105mm)	4 " (100mm)
WFR2-450-100-02	4 1/2 " (115mm)	4 " (100mm)
WFR2-475-100-02	4 3/4 " (120mm)	4 " (100mm)
WFR2-500-100-02	5 " (125mm)	4 " (100mm)
WFR2-525-100-02	5 1/4 " (130mm)	4 " (100mm)
WFR2-550-100-02	5 1/2 " (140mm)	4 " (100mm)
WFR2-575-100-02	5 3/4 " (145mm)	4 " (100mm)
WFR2-600-100-02	6 " (150mm)	4 " (100mm)

Testing and Standards

EMSHIELD WFR2 has been tested and certified under UL 2079.

EMSHIELD WFR2 meets the requirements of ASTM E1966, ASTM E119 and ASTM E1399.

UL 2079, like ASTM E1966, was developed to encompass the fire testing of ASTM E119 and the movement cycling regime of ASTM E1399.

Warranty

Standard or project-specific warranties are available from EMSEAL on request. This product can only perform its designed function if it, and the joint-gap into which it is installed, is sized to suit anticipated joint movements in consideration of the movement capability of the product and in consideration of the temperature at time of installation, and if it is installed in strict accordance with EMSEAL's installation instructions.

Availability & Price

EMSHIELD WFR2 is available for shipment domestically and internationally. Prices are available from local representatives and/or directly from the manufacturer. The product range is continually being updated, and accordingly EMSEAL reserves the right to modify or withdraw any product without prior notice.